

Loop Hanger Surge Restraint

For Fire Sprinkler Systems

Features

- Restricts the upward surge movement of activated fire sprinkler systems
- Meets NFPA® 13
- One LHSR6 fits the One-Piece Loop Hanger – 1/2" through 2" sizes – the widest range available
- Grips the loop hanger – not the nut – allowing fine tuning adjustments
- Installs without tools



**One size
fits all.**



Installs easily – before or after pipe installation.
Grips the loop hanger and not the nut, allowing for adjustment.



Other Fire Protection Fastening Solutions



PH/SW-FP

The Multi-Flange Rod Hanger (PH/SW-FP) is UL® Listed for fire protection applications on C or Z purlin structures. It installs quickly and easily, with a special swivel feature option that allows straight drops from pitched roofs. Supports up to 3" sprinkler piping.

SO Series

The Stand-Off Strap Hanger (SO Series) is the fastest offset CPVC support available and it complies with the static load requirements of NFPA® 13. Mount CPVC fire protection pipe to structural wood or composite wood joists.



The unique shape quickly positions CPVC pipe 1-1/2" off the surface – eliminating the need for wood blocking materials, spacers or backup blocks.



304B2

Protect plumbing and CPVC fire protection installations with the Press-On Protection Plate for wood and metal studs, part of the CADDY® line of products. Breakable tabs permit multiple plates to be connected for use with double stud. And, best of all, this plate can be installed with no installation tools.

cULus is a registered certification mark of UL LLC.

WARNING
ERICO products shall be installed and used only as indicated in ERICO's product instruction sheets and training materials. Instruction sheets are available at www.erico.com and from your ERICO customer service representative). Improper installation, misuse, misapplication or other failure to completely follow ERICO's instructions and warnings may cause product malfunction, property damage, serious bodily injury and death.

Copyright ©2014 ERICO International Corporation. All rights reserved.
CADDY, CADWELD, CRITEC, ERICO, ERIFLEX, ERITECH, and LENTON are registered trademarks of ERICO International Corporation.
NFPA is a registered trademark of the National Fire Protection Association. UL is a registered trademark of Underwriters Laboratories, Inc.

Loop Hanger Surge Restraint

For Fire Sprinkler Systems

The LHSR6 is a snap-in solution that is easy to install without tools – providing increased jobsite efficiency. The flat bottom plate is designed to prevent 'rough cut' edge of the threaded rod from puncturing the pipe – improving system integrity. The LHSR6 is for use with Loop Hangers Model #112, part of the CADDY® line of products




The improved Loop Hanger model #112, features a retained insert nut to help ensure that the loop hanger and the insert nut stay together. No more searching the bottom of the box for loose insert nuts.



Retained insert.



UPC No. 782856-	Part No.	Description	
45298	LHSR6	Loop Hanger Surge Restraint	100